

Additional Valves



CUSTOMER TO SPECIFY IF FLANGE ENDS ARE TO BE MATED TO FIXED FLANGES OR FLOATING FLANGES PRIOR TO ORDERING.

FLANGED CHECK VALVE

- SOLID CAST CONES, SEAT, DISC & MACHINED HINGE PIN
- DESIGNED WITH OFF-CENTER PIVOT TO AID THE OPERATION AT LOW PRESSURE DIFFERENTIALS
- RESILIENT SEAT OPTIONS AVAILABLE
- SIZES RANGE FROM 2" - 30"



WAFER CHECK VALVE

- SOLID CAST BODY, CAST DISC & MACHINED HINGE PIN
- DISC IS LIGHTER IN DESIGN ALLOWING IT TO OPEN QUICKER AND EASIER
- WAFER STYLE BODY REDUCES VALVE WEIGHT
- RESILIENT SEAT OPTIONS AVAILABLE
- SIZES RANGE FROM 2" - 24"

SAMPLING VALVE



- DESIGNED FOR INSTALLATION IN STOCK LINES OR TANKS WHERE OCCASIONAL SAMPLING OF CONTENTS IS REQUIRED
- VALVE IS THREADED FOR INSTALLATION IN A HALF COUPLING THAT HAS BEEN WELDED INTO THE LINE OR TANK
- 1-1/2" AND 2" NPT THREADED END CONNECTIONS



PNEUMATIC AIR CYLINDERS

- SIZES AVAILABLE FROM 5" BORE TO 20" BORE FOR VALVES RANGING FROM 2" - 42"
- PRE-DRILLED HOLES FOR DIRECT MOUNTING TO NPV PRODUCTS
- QUAD RING PISTON SEAL FOR OPTIMUM SEALING



TRANSMITTER ISOLATION VALVE

- CAST ONE PIECE BODY
- RATCHET OPERATOR STANDARD, LEVER OPERATOR AVAILABLE
- DESIGNED FOR FLUSH MOUNTING TO TANKS WITH SIDE FLANGE BOLT CIRCLE



LINE BLINDS

- USED TO ISOLATE PIPELINES WITH ZERO LEAKAGE
- SIZES RANGE FROM 2" - 24"



North Port Valves

INDUSTRY'S CHOICE FOR SERVICE & QUALITY

